

# ID Platform FAP20



P/N: IDP-FAP20-35030021XX90

#### PHYSICAL CHARACTERISTICS

**DIMENSIONS & WEIGHT** 288 mm x 147 mm x 25 mm | 785 grams

SCREEN 7" TFT LCD | 1280x800 HD | 400 cd/m² | 16.7M Colors | Touch/Panel Glass: 0.7mm Corning Glass

GFF Sensor Type | Capacitive 5 Points Multi Touch | Possibility to add an Extra Tempered Glass Protection

CAMERA 8MP Fixed Focus Front Camera (IMX219) | 13MP Auto Focus Rear Camera (OV13850) | Dual Flash Light

BATTERY 1 x 12600 mAh | Removable battery | Robust 2.5mm | Power Jack socket for 12V / 2.5A charger

**EXTENSION AND**USB type C for service port | USB type A host connector 2 Micro SIM/USIM slots (ISO7816) | 1 Micro SD Slot

AUDIO Audio Jack: Headset with Microphone | Bluetooth Headset Compatible | Loudspeaker 1W

SENSORS Light Sensor | Magnetometer | G sensor | Gyroscope | Vibrator

#### PERFORMANCE CHARACTERISTICS

**PROCESSOR** Octa Core SDM450 @ 1.8 GHz

**MEMORY** 16 GB eMMC + 2 GB DDR3 | MicroSD TFLASH: Up to 256 GB

**OPERATING SYSTEM** Android 9

#### **USER ENVIRONMENT**

IP SEALING

IP54 (The protection class against dust and water can be increased by a protective case to IP65 or even IP67)

TEMPERATURES

Operating Temperature: -20°C to +60°C | Storage Temperature: -30°C to +60°C | Humidity: 5 to 95% non-condensing

## **WIRELESS COMMUNICATIONS**

**BLUETOOTH** 4.0 - Low Energy

**WLAN** WiFi 802.11 a/b/g/n/ac - Direct - HotSpot

**WWAN** 2G supported frequency bands: GSM(850), EGSM(900), DCS(1800), PCS(1900)

3G supported frequency bands: WCDMA Band 1,2,5,8

4G supported frequencies bands: LTE-FDD Band 1, 3, 7, 20, 28 A&B

LTE-TDD Band 40

INTEGRATED GPS GPS | A-GPS | GLONASS | BeiDou (active antenna)

### **IDENTIFICATION MODULE**

CONTACTLESS CARD NFC: NXP IC on board (PN80T:PN553 + P73N2M0) Compliant with ISO14443 A/B and ISO15693

**READER** With Secure Element - Read / Write mode - HEC - Card Emulation

SECURE ELEMENT P73N2MP (NFC IC) | SIM/USIM socket (SWP IF with NFC IC + ISO7816 IF with CPU)

### **BIOMETRICS READER**

FINGERPRINT SCANNER Suprema BM-Slim2 | Optical

Certified FBI PIV / FAP20 | Active area: 15.24 mm x 20.32 mm | Resolution: 500 PPI

IRIS SCANNER 2.4MP Rear Camera (IMX132) | Dual IR LED (SFH4787S)

## REGULATORY

**CERTIFICATION** EU: CE certification | Other Countries: on demand